LEVEL	MILD					MODERATE			
RANGE		TEMPERATURE RANGE : 0 to -5 DEGREE CELSIUS				TEMPERATURE RANGE : -5 to -15 DEGREE CELSIUS			
LINING TYPES		NAPPED THERMAL INTERIOR	COTTON FLEECE TR2 Heat lok	FOAM	7GG THERMAL ACRYLIC TERRY LINER	C40 THINSULATE	SHERPA	C100-C150, G100 THINSULATE	COLD MX™
PHOTO OF LINING									
COATING DESCRIPTIC FEATURES	DN/	Minimum warmth. The fibres of seamless string-knit shells are brushed to create a warm lining	Minimum warmth. A lightweight 100% cotton, combed to provide insulation and excellent dexterity	Medium warmth. A polyurethane foam layer, sometimes cov- ered by fleece or lined with nylon	Minimum warmth. A regular cotton, wool or polyester fabric that is coated on one side with acrylic foam	Medium warmth. Designed by 3M, Thinsulate [™] fibres are fine, making them ideal for trapping insulating air and re- flecting back the body's radiant heat. Thinsulate [™] insulation provides more warmth with less bulk.	Excellent warmth. A nubby, soft pile material that provides a high degree of warmth. The sherpa material is often made from a blend of fibres including acrylic and polyester.	Excellent warmth. Designed by 3M, Thinsulate [™] fibres are fine, making them ideal for trapping insulating air and reflecting back the body's radiant heat. Thinsulate [™] insulation provides more warmth with less bulk.	Thin and dense fiber thermal insulation for great dexterity which offers wind/water resis- tant, thermal protection, and antibacterial properties.
		300i (Napped) 320i (Napped) 330 (Napped) temperature ranges of an differ between user			9393 (Acrylic) 9392 (Napped Thermal) 9403 (Acrylic) 491 (Acrylic) 9390 (Terry Liner) 9405 (Terry Liner) 9408 9361 9398TPR	9576 (C40) 9586 (C40) 9376 (C40) 9913 (C40) 9005W (C40) 9584 (C40) 9578 (C40) 9N660 (C40) 9WB67 (C40) 1935 (C40)	94002 (Sherpa) 94003i (Sherpa) 94004i (Sherpa) 9200i (Sherpa) 9200i F (Sherpa) 9246i (Sherpa) 9346 (Sherpa) 9590 (Sherpa) 9591 (Sherpa) 94001 (Sherpa)	9542W (C100) 9545 (C100) 9577 (C100) 9587 (C100) 94006HW (C100) 94006HW (C100) 94106HHV (C100) 9549 (C100) 93777 (C100) 9407RT (C100) 1034T (C100) 1034T (C100) 92757 (C100) 9525T (C100) 9525T (C100) 9502 (C150) 9503 (C150) 957831FG (C100) 95782 (C100) 95782 (C100) 95782CR (C100) 95782CR (C100) 95782CR (C100) 95782CR (C100) 95782CR (C100) 95785 95	91051 9585 9499 9500 9382 9381
CHARACTERISTICS	Warmth	FAIR	FAIR	GOOD	FAIR	GOOD	EXCELLENT	EXCELLENT	EXTREME
	Dexterity	EXCELLENT	EXCELLENT	GOOD	EXCELLENT	GOOD	FAIR	FAIR	FAIR

EXTREME

TEMPERATURE RANGE : -15 to -20 DEGREE CELSIUS

C200-C300 Thinsulate



Extreme warmth. Designed by 3M Thinsulate[™] fibres are fine, making them ideal for trapping insulating air and reflecting back the body's radiant heat. Thinsulate[™] insulation provides more warmth with less bulk.

9241T (C300) 9302 (C300) 9303 (C200) 95783G (C300) 95783 (C300)





EXTREME FAIR